
Belt and Disk Sander Theory Test

Name of Student	
Class	
Grade	

NOTE: Students must achieve 80% or higher to pass the test

1. Label the parts of the Belt & Disk Sander from the following list: (Fence, Sand Belt, Emergency Stop, Sand Disk, Adjustable Fence, Table Adjuster, Stand)



	16 mar
3.	Outline three safety measures that must be undertaken before operating the Belt and Dis Sander:
	15 mar
	15 mar
4.	Why is it important never to reach across the Belt and Disk Sander to turn it off?
4.	
4.	

NOTE: The following questions are all multiple choice. Please place a tick/mark in the beside the answer you feel is the most suitable .	box
5. When changing the Belt or Disk what is the first thing that should be done to the	Sander?
A: All dust should be brushed off machine	
C B: It should be plugged out	
C C: The fence should be adjusted for easier access	
C D: Run Sander at a low speed	
	8 marks
9. What angle can the disk table be adjusted to on most Belt and Disk Sanders? C A: 90 Degrees	
C B: 70 Degrees	
C C: 60 Degrees	
C D: 45 Degrees	
	8 marks
6. When using the Belt and Disk Sander it is important to:	
C A: Never wear baggie clothes	
C B: Keep two hands on the workpiece	
C C: Turn off machine when finished sanding	
C D: All of the above	
	8 marks
7. When the Belt and Disk Sander is in operation it is important to:	
C A: Maintain full concentration and act safely	
© B: Keep your friends updated on how the machine is running	
C C: Start putting on your Personal Protective Equipment (PPE)	
O D: Adjust the table height	
	8 marks

Date Test (Completed:			
Student Si	gnature:			
	Pass	Y THE TEACHER Fail		
Teacher Si Date:	gnature:			